


## KUVE25-B-S INA

Linear guides

TYPE: Monorail guidance systems, Recirculating balls, High vertical load carrying capacity type, Self-aligning type, Square type, Low, Ball slide length - standard, Mounting tap



### Technical specification

#### DIMENSIONS, MM

B1	48,000
H	33,000
L	81,600
B	35,000
J	35,000
L1	60,000
B2	6,500
B3	23,000
B4	12,500
H1	26,000
H2	7,000
T	12,000
T1	7,000
f	11,000
C	60,000

#### DIMENSIONS, MM

d1	7,000
d2	11,000
h	18,000
h1	9,000
L max	3960,000
aL	20,000
aR	20,000
F	M6x1x9

#### WEIGHT

Slide weight	0,510
Rail weight	3,100

#### MANUFACTURER

[INA](#)

#### INTERCHANGE

ABC	<a href="#">LS25AL</a>
NSK	<a href="#">LS25AL</a>

**INTERCHANGE**

THK	<a href="#">SR25WY</a>
IKO	<a href="#">LWES25</a>
HIWIN	<a href="#">EGH25CA</a>
STAR	<a href="#">1694-2</a>
Rockford Linear Motion	<a href="#">RPG25SW</a>
NB	<a href="#">SGL25TF</a>
THOMSON	<a href="#">AT 25F</a>