

SGL15HTE NB

Linear guides

TYPE: Monorail guidance systems, Recirculating balls, High vertical load carrying capacity type, Self-aligning type, Flanged type, Low, Ball slide length - standard, Mounting tap



Technical specification

DIMENSIONS, MM

| | |
|----|--------|
| B1 | 47,000 |
| H | 24,000 |
| L | 55,000 |
| B | 38,000 |
| J | 30,000 |
| L1 | 39,000 |
| B3 | 15,000 |
| B4 | 16,000 |
| H1 | 19,400 |
| H2 | 4,600 |
| T | 8,000 |
| T1 | 4,500 |
| f | 3,300 |
| C | 60,000 |
| d1 | 4,500 |

DIMENSIONS, MM

| | |
|-------|----------|
| d2 | 7,500 |
| h | 15,000 |
| h1 | 5,300 |
| L max | 2000,000 |
| aL | 20,000 |
| aR | 20,000 |
| F | M5x0.8x8 |

WEIGHT

| | |
|--------------|-------|
| Slide weight | 0,170 |
| Rail weight | 1,600 |

MANUFACTURER

[NB](#)

INTERCHANGE

| | |
|-----|------------------------|
| ABC | LH15EL |
| NSK | LH15EL |
| THK | HSR15A |

INTERCHANGE

| | |
|---------------------------|---------------------------|
| IKO | LWHT15..B |
| HIWIN | HGW15CA |
| STAR | 1651-1 |
| Rockford Linear Motion | RPG15HA |
| INA | KUVE15-B |
| SCHNEEBERGER | BMA 15 |