


LH20HL NSK

Linear guides

TYPE: Monorail guidance systems, Recirculating balls, High vertical load carrying capacity type, Self-aligning type, Flanged type, Low, Ball slide length - long, Mounting bolt hole



Technical specification

DIMENSIONS, MM

B1	63,000
H	30,000
L	91,800
B	53,000
J	40,000
L1	72,000
B2	5,000
B3	20,000
B4	21,500
H1	25,000
H2	5,000
T	10,000
T1	5,000
f	11,000
C	60,000

DIMENSIONS, MM

d1	6,000
d2	9,500
h	18,000
h1	8,500
L max	3960,000
aL	20,000
aR	20,000
F	6x10

WEIGHT

Slide weight	0,650
Rail weight	2,600

MANUFACTURER

[NSK](#)

INTERCHANGE

ABC	LH20HL
THK	HSR20LB

INTERCHANGE

IKO	LWHG20
HIWIN	HGW20HB
STAR	1653-8
INA	KUSE 20L
THOMSON	AG20BA

CALCULATION DATA

Basic dynamic load rating, C	18,200 kN
Basic static load rating, Co	39,500 kN
Static permissible moment, Ma	0,345 kN-m
Static permissible moment, Mb	0,345 kN-m
Static permissible moment, Mc	0,305 kN-m

INCLUDED PRODUCTS

LAH20HL