

## SH25FL NSK

Linear guides

TYPE: Monorail guidance systems, Recirculating balls, High vertical load carrying capacity type, Self-aligning type, Flanged type, Low, Ball slide length - standard, Mounting bolt hole, Low noise, smooth operation type



### Technical specification

## DIMENSIONS, MM

B1	70,000
H	36,000
L	79,000
B	57,000
J	45,000
L1	58,000
D2	11,500
B2	6,500
B3	23,000
B4	23,500
H1	29,000
H2	7,000
T	11,000
T1	6,000
f	11,000

## INTERCHANGE

THK	<a href="#">SHS25C</a>
STAR	<a href="#">1651-2</a>

## CALCULATION DATA

Basic dynamic load rating, C	19,800 kN
Basic static load rating, Co	36,000 kN
Static permissible moment, Ma	0,284 kN-m
Static permissible moment, Mb	0,284 kN-m
Static permissible moment, Mc	0,333 kN-m

## INCLUDED PRODUCTS

SAH25FL

## DIMENSIONS, MM

C	60,000
d1	7,000
d2	11,000
h	22,000
h1	9,000
L max	3960,000
aL	20,000
aR	20,000
F	7x10

## WEIGHT

Slide weight	0,630
Rail weight	3,600

## MANUFACTURER

[NSK](#)

## INTERCHANGE

ABC	<a href="#">SH25FL</a>
-----	------------------------