

## SH30FL NSK

Linear guides

TYPE: Monorail guidance systems, Recirculating balls, High vertical load carrying capacity type, Self-aligning type, Flanged type, Low, Ball slide length - standard, Mounting bolt hole, Low noise, smooth operation type



### Technical specification



## DIMENSIONS, MM

B1	90,000
H	42,000
L	98,600
B	72,000
J	52,000
L1	72,000
D2	14,000
B2	9,000
B3	28,000
B4	31,000
H1	33,000
H2	9,000
T	11,000
T1	7,000
f	11,000

## INTERCHANGE

THK	<a href="#">SHS30C</a>
STAR	<a href="#">1651-7</a>

## CALCULATION DATA

Basic dynamic load rating, C	27,600 kN
Basic static load rating, Co	49,300 kN
Static permissible moment, Ma	0,441 kN-m
Static permissible moment, Mb	0,441 kN-m
Static permissible moment, Mc	0,549 kN-m

## INCLUDED PRODUCTS

SAH30FL

## DIMENSIONS, MM

C	80,000
d1	9,000
d2	14,000
h	26,000
h1	12,000
L max	4000,000
aL	20,000
aR	20,000
F	9x12

## WEIGHT

Slide weight	1,200
Rail weight	5,200

## MANUFACTURER

[NSK](#)

## INTERCHANGE

ABC	<a href="#">SH30FL</a>
-----	------------------------

