

SH15HL NSK

Linear guides

TYPE: Monorail guidance systems, Recirculating balls, High vertical load carrying capacity type, Self-aligning type, Flanged type, Low, Ball slide length - long, Mounting bolt hole, Low noise, smooth operation type



Technical specification



DIMENSIONS, MM

B1	47,000
H	24,000
L	74,000
B	38,000
J	30,000
L1	58,000
D2	7,500
B2	4,500
B3	15,000
B4	16,000
H1	19,400
H2	4,600
T	8,000
T1	4,500
f	3,300

INTERCHANGE

THK [SHS15LC](#)

CALCULATION DATA

Basic dynamic load rating, C	10,900 kN
Basic static load rating, Co	23,500 kN
Static permissible moment, Ma	0,158 kN-m
Static permissible moment, Mb	0,157 kN-m
Static permissible moment, Mc	0,143 kN-m

INCLUDED PRODUCTS

SAH15HL

DIMENSIONS, MM

C	60,000
d1	4,500
d2	7,500
h	15,000
h1	5,300
L max	2000,000
aL	20,000
aR	20,000
F	4.5x7

WEIGHT

Slide weight	0,250
Rail weight	1,600

MANUFACTURER

[NSK](#)

INTERCHANGE

ABC [SH15HL](#)

