


## SS30KL NSK

Linear guides

TYPE: Monorail guidance systems, Recirculating balls, High vertical load carrying capacity type, Self-aligning type, Flanged type, Low, Ball slide length - short, Mounting bolt hole, Compact, Low noise, smooth operation type



### Technical specification

#### DIMENSIONS, MM

|    |        |
|----|--------|
| B1 | 90,000 |
| H  | 9,000  |
| L  | 67,400 |
| B  | 72,000 |
| L1 | 42,000 |
| D2 | 14,000 |
| B2 | 9,000  |
| B3 | 28,000 |
| B4 | 31,000 |
| H1 | 33,000 |
| H2 | 9,000  |
| T  | 11,000 |
| T1 | 8,000  |
| f  | 11,000 |
| C  | 80,000 |

#### DIMENSIONS, MM

|       |          |
|-------|----------|
| d1    | 7,000    |
| d2    | 11,000   |
| h     | 23,000   |
| h1    | 9,000    |
| L max | 4000,000 |
| aL    | 20,000   |
| aR    | 20,000   |
| F     | 9x12     |

#### WEIGHT

|              |       |
|--------------|-------|
| Slide weight | 0,760 |
| Rail weight  | 4,800 |

#### MANUFACTURER

[NSK](#)

#### INTERCHANGE

|     |                        |
|-----|------------------------|
| ABC | <a href="#">SS30KL</a> |
|-----|------------------------|

**CALCULATION DATA**

|                               |            |
|-------------------------------|------------|
| Basic dynamic load rating, C  | 14,500 kN  |
| Basic static load rating, Co  | 22,900 kN  |
| Static permissible moment, Ma | 0,098 kN-m |
| Static permissible moment, Mb | 0,098 kN-m |
| Static permissible moment, Mc | 0,216 kN-m |

**INCLUDED PRODUCTS**

SAS30KL